



TAP CHUCKS: AMERICAN STANDARD



American Standard Taps, Positive Drive (PD)

Chuck Size	Tap Size	Shank Ø (ins)	Square A/F (ins)	PD
0	0 - 6	.141	.110	X600300
	8	.168	.131	X600301
	10	.194	.152	X600302
	12	.220	.165	X600303
	14, 1/4	.255	.191	X600304
	5/16	.318	.238	X600305
1	0 - 6	.141	.110	X610300
	8	.168	.131	X610301
	10	.194	.152	X610302
	12	.220	.165	X610303
	14, 1/4	.255	.191	X610304
	5/16	.318	.238	X610305
	7/16	.323	.242	X610306
	1/2	.367	.275	X610307
	3/8	.381	.286	X610308
	9/16	.429	.322	X610309
2	5/16	.318	.238	X620305
	7/16	.323	.242	X620306
	1/2	.367	.275	X620307
	3/8	.381	.286	X620308
	9/16	.429	.322	X620309
	5/8	.480	.360	X620310
	11/16	.542	.406	X620318
	3/4	.590	.442	X620311
	13/16	.652	.489	X620319
	7/8	.697	.523	X620312
3	5/8	.480	.360	X630310
	11/16	.542	.460	X630318
	3/4	.590	.442	X630311
	13/16	.652	.489	X630319
	7/8	.697	.523	X630312
	15/16	.760	.570	X630320
	1	.800	.600	X630313
	1 1/8	.896	.672	X630314
	1 1/4	1.021	.766	X630315
	1 3/8	1.108	.831	X630316

American Standard Taps, Slipping Clutch Drive (SCD)

Chuck Size	Tap Size	Shank Ø (ins)	Square A/F (ins)	SCD
0	0 - 6	.141	.110	X602300
	8	.168	.131	X602301
	10	.194	.152	X602302
	12	.220	.165	X602303
	12, 1/4	.255	.191	X602304
	5/16	.318	.238	X602305
1	0 - 6	.141	.110	X612300
	8	.168	.131	X612301
	10	.194	.152	X612302
	12	.220	.165	X612303
	12, 1/4	.255	.191	X612304
	5/16	.318	.238	X612305
	7/16	.323	.242	X612306
	1/2	.367	.275	X612307
	3/8	.381	.286	X612308
	9/16	.429	.322	X612309
2	5/16	.318	.238	X622305
	7/16	.323	.242	X622306
	1/2	.367	.275	X622307
	3/8	.381	.286	X622308
	9/16	.429	.322	X622309
	5/8	.480	.360	X622310
	11/16	.542	.406	X622318
	3/4	.590	.442	X622311
	13/16	.652	.489	X622319
	7/8	.697	.523	X622312
3	5/8	.480	.360	X632310
	11/16	.542	.460	X632318
	3/4	.590	.442	X632311
	13/16	.652	.489	X632319
	7/8	.697	.523	X632312
	15/16	.760	.570	X632320
	1	.800	.600	X632313
	1 1/8	.896	.672	X632314
	1 1/4	1.021	.766	X632315
	1 3/8	1.108	.831	X632316